

NVR7808/7816/7832/7864

8/16/32/64 Channel 2U Network Video Recorder



- > Up to 4/8/16 cameras with 1080p realtime preview
- > H.264 dual-stream video compression
- > Full channel @D1(4CIF) realtime recording > HDMI / VGA / TV/Spot simultaneous video output
- > All channel synchronous realtime playback, GRID interface & smart search > 3D intelligent positioning with Dahua PTZ dome camera
- > Support 4 SATA HDD up to 16TB, 1 eSATA up to 16TB, 2 USB2.0
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

型號	DH-NVR7808	DH-NVR7816	DH-NVR7832	DH-NVR7864
系統				
主處理器	雙核心嵌入式處理器			
操作系統	嵌入式 LINUX			
視頻和音頻				
IP 攝影機輸入	8 通道	16 路	32 路	64 路
雙向通話	1 路輸入 · 1 路輸出 · BNC			
顯示				
接口	1 個 HDMI · 1 個 VGA · 1TV			
解析度	1920×1080 · 1280×1024 · 1280×720 · 1024×768			
顯示分割	1/4/8/9	1/4/8/9/16	1/4/8/9/16/25/36	1/4/8/9/16/25/36
OSD	攝影機標題 · 時間 · 視頻丟失 · 攝影機鎖定 · 移動偵測 · 錄影			
記錄				
壓縮	H.264 / MJPEG			
分辨率	1080P (1920×1080) / 720P (1280×720) / D1 (704×704 分之 576×480) 。			
備案率	192Mbps			
比特率	48~8192kbps			
錄像模式	手動 · 定時 (正常 (連續) · MD · 警報) · 停止			
記錄間隔	1~120 分鐘 (默認 : 60 分鐘) · 預錄 : 1~30 秒			
視頻檢測和報警				
觸發事件	錄影 · PTZ · 巡迴 · 報警 · 視頻推送 · 電子郵件 · FTP · 蜂鳴器和螢幕提示			

NVR7808/7816/7832/7864

視頻檢測	動態檢測 · MD 區域：396 (22×18) · 視頻丟失和相機空白			
報警輸入	8 通道	16 路	16 路	16 路
繼電器輸出	3 通道	6 通道	6 通道	6 通道
回放和備份				
同步播放	1/4/9	1/4/9/16	1/4/9/16	1/4/9/16
搜索模式	時間/日期 · 鬧鐘 · 管理層討論與分析精確搜索 (精確到秒) · 智能搜索			
播放功能	播放 · 暫停 · 停止 · 倒帶 · 快放 · 慢放 · 下一個文件 · 上一個文件 · 然後攝影機 · 前攝影機 · 全螢幕 · 重複 · 隨機播放 · 備份選擇 · 數位變焦			
備份模式	USB 設備/ eSATA 設備/內置 SATA 燒錄機/網絡			
網絡				
以太網	2 個 RJ-45 端口 (10/100 / 1000Mbps 的)			
網絡功能	HTTP · TCP / IP 協議 · IPv4 / IPv6 雙 · UPNP · RTSP · UDP · SMTP · NTP · DHCP · DNS · IP 過濾 · PPPOE · DDNS · FTP · 報警服務器 · IP 搜索 (支持大華網絡攝像機 · 硬盤錄像機 · 網絡視頻服務器等。)			
最大用戶訪問	128 用戶			
智慧型手機	iPhone · iPad · Android · Windows Phone			
存儲				
內置硬盤	8 個 SATA 端口 (8HDDs 或 6HDDs + 1CD / DVD-RW) · 高達 32TB · RAID (冗餘)			
移動硬盤	1 個 eSATA 接口			
輔助接口				
USB	4 端口 (2 個後置) · USB2.0 接口			
RS232	1 端口 · PC 和鍵盤			
RS485	1 端口 · PTZ 控制			

.....